(3 Hours)

Q.P. Code: 50777

[Total Marks:80]

| N. | B.: 1 |) Question No. 1 is compulsory. | |
|------|-------|---|-------|
| | 2 | Attempt any three questions out of the remaining five questions. | |
| | 3 | Assume suitable data wherever necessary. | 500 |
| | | | |
| 1. | | | 20 |
| | a) | Explain how quantization helps in noise removal. | 2, 2 |
| | b) | Explain why the local oscillator frequency is always chosen as f_s+f_{IF} and not f_s-f_{IF} ? | |
| | c) | Explain noise triangle in FM. Determine the everall point forter and point for three considerable and with | 0 |
| | d) | Determine the overall noise factor and noise figure for three cascade amplifiers with the following parameters: | AT |
| | | A_1 =6dB, A_2 =15dB A_3 =10dB | 0 1 |
| | | NF ₁ =10dB NF ₂ =6dB NF ₃ =10dB | 7,69 |
| | e) | Calculate percentage saving in AM modulated wave to a depth of 100 percent when the | |
| | | carrier and one of the sidebands are suppressed. Compare AM with SSB-SC. | £ 62. |
| 2. | a) | With the help of a neat bock diagram explain the FM transmitter using Armstrong | 5 |
| | | method of FM generation. | |
| | b) | In a super-heterodyne receiver having no RF amplifier, the loaded Q of the antenna | 5 |
| | | coupling circuit is 100. If the IF is 455kHz, calculate: 1) The image frequency and its | |
| | | rejection ratio for the tuning at 1044kHz. 2) The image frequency and its rejection ratio for the tuning at 30MHz. | |
| | c) | With a neat block diagram explain the working of super-heterodyne receiver, with | 10 |
| | C) | waveforms at the output of each block. Explain the functions of each block. | 10 |
| 3. | a) | Explain the terms with reference to Radio Receivers: Selectivity, Sensitivity, Fidelity | 10 |
| | • ` | AGC and Double spotting. | 10 |
| | b) | Explain the frequency discriminators with the help of neat diagrams. | 10 |
| 4. | a) | Explain PAM, PWM and PPM generation with relevant waveforms. | 10 |
| | b) | Explain natural sampling and flat top sampling. What is aliasing error? How it can be | 10 |
| | | overcome? | |
| | Á | | |
| 5. | | Derive the expression for the signal to quantization noise ratio in PCM. | 5 |
| | b) | | 5 |
| V DY | 199 | deviation is 4.8kHz. Calculate the modulation index and the bandwidth required. If the | |
| 2// | V V V | modulating frequency is halved, what is the new bandwidth? Explain the working of Delta Modulation with a neat block diagram and showing | 10 |
| | (c) | proper waveforms. | 10 |
| 6. | a) | Explain FDM with a neat block diagram. Give its applications. | 10 |
| 3 | b) | Draw block diagram of PCM transmitter and receiver and explain the function of each | 10 |
| | | block | |
| 200 | 35 | | |
| 60°C | 6,6 | ************* | |