

Q. P. Code : 600902

[3 Hours]

[Total Marks:80]

- Notes:**
- 1) Question no.1 is **compulsory**.
  - 2) Attempt any **THREE** from question no.2 to 6.
  - 3) Use illustrative diagrams wherever possible.
  - 4) Use of Steam table is permitted.
  - 5) Assume suitable data wherever required.

1. Solve any **Four** :- 20
  - a) Draw a neat boiling curve for water and mark the different boiling regimes.
  - b) A steel ball 50mm in diameter and at 900°C is placed in still atmosphere of 30°C. Calculate the initial rate of cooling of the ball in °C/min. Take  $\rho = 7800 \text{ kg/m}^3$ ,  $C = 2 \text{ kJ/kg}^\circ\text{C}$  (for steel),  $h = 30 \text{ W/m}^2 \text{ }^\circ\text{C}$ . Neglect internal thermal resistance.
  - c) Explain non dimensional numbers used in convection heat transfer.
  - d) Explain briefly the term thermal capacity and thermal diffusivity of material.
  - e) Define intensity of radiation. What is a solid angle? What is its unit?
  
2. a) A wall of a furnace is made up of inside layer of silica brick 120 mm thick covered with a layer of magnesite brick 240 mm thick. The temperature at inside surface of silica brick wall and outside surface of magnesite brick wall are 725°C and 110°C respectively. The contact thermal resistance between the two walls at the interface is 0.0035°C/W per unit wall area. If thermal conductivities of silica and magnesite bricks are 1.7 W/m°C and 5.8 W/m°C, calculate. 10
  - (i) The rate of heat loss per unit area of walls.
  - (ii) The temperature drop at interface.
- b) Derive the formula for rate of heat transfer for an insulated tip fin from the differential equation 10

$$\frac{d^2 \theta}{dx^2} - m^2 \theta = 0$$
  
3. a) Air at 30°C flows with a velocity of 2.8 m/s over a plate 1000 mm (length) X 600 mm (width) X 25mm (thickness). The top surface of the plate is maintained at 90°C. If the thermal conductivity of the plate material is 25 W/m°C, calculate: i) heat lost by the plate; ii) bottom temperature of the plate for the steady state condition. The thermo – physical properties of air at mean film temperature at 60°C are  $\rho = 1.06 \text{ kg/m}^3$ ,  $k = 0.02894 \text{ W/m}^\circ\text{C}$ ,  $C_p = 1.005 \text{ kJ/kg}^\circ\text{C}$ ,  $Pr = 0.696$ ;  $\nu = 18.97 \times 10^{-6} \text{ m}^2/\text{s}$ . Choose the appropriate relation from the following: 10

$$\overline{Nu} = 0.664 (Re_L)^{1/2} (Pr)^{1/3} \text{ - For Laminar flow;}$$

$$\overline{Nu} = 0.036 (Re_L)^{0.8} (Pr)^{1/3} \text{ - For Turbulent flow}$$
- b) With the help of dimensional analysis method prove that for free convection 10

$$Nu = \text{constant} \times (Gr.)^m \times (Pr.)^n$$

[TURN OVER

4. a) State and explain the reciprocity theorem. Derive the equation  $A_1 F_{1-2} = A_2 F_{2-1}$ . 10
- b) An electric wire of 0.25mm diameter,  $\epsilon=0.4$  is placed within a tube of 2.5 mm diameter,  $\epsilon=0.6$  having negligible thickness. This tube in turn is placed concentrically within a tube of 5 mm diameter,  $\epsilon=0.7$ . Annular spaces can be assumed to be evacuated completely. If the surface temperature of the outer tube is maintained at  $5^\circ\text{C}$ , what must be the temperature of wire so as to maintained the temperature of inner tube at  $120^\circ\text{C}$ ? 10
5. a) Derive the expression for log mean temperature difference in a counter flow heat exchanger. State your assumption. 08
- b) In a certain double pipe heat exchanger hot water flows at the rate of 50000 kg/hr and gets cooled from  $95^\circ\text{C}$  to  $65^\circ\text{C}$ . At the same time 50000 kg/hr of cooling water at  $30^\circ\text{C}$  enters the heat exchanger. The flow conditions are such that overall heat transfer coefficient remains constant at  $2270\text{W/m}^2\text{K}$ . Determine the heat transfer area required and the effectiveness, assuming two streams are in parallel flow. Assuming for the both streams  $C_p = 4.2\text{ kJ/kg K}$ . 08
- c) Explain Heat Exchangers effectiveness. 04
6. a) Write short note on **any Two** of the following - 08
- Heisler Chart.
  - Explain efficiency and effectiveness of fin.
  - Time constant of thermocouple.
- b) Explain Hydrodynamic and thermal boundary layer. 04
- c) A steel rod ( $K=32\text{ W/m}^\circ\text{C}$ ), 12 mm in diameter and 60 mm long, with an insulated ends to be used as spine. It is exposed to surroundings with a temperature of  $60^\circ\text{C}$  and a heat transfer coefficient of  $55\text{ W/m}^2\text{C}$ . The temperature at the base of the fin is  $95^\circ\text{C}$ . Determine- 08
- The fin efficiency.
  - The temperature at the edge of the spine:
  - The heat dissipation.