

Duration: 3 hours

Total Marks: 80

- N. B. (i) Question number **one is compulsory.**
(ii) Answer any **three** questions from the rest.
(ii) Assume suitable data wherever necessary.

Q. 1 Write short note on any **four** **20**

- (a) List out types of supports. Explain any one in detail.
- (b) Explain constructional features of high pressure vessel
- (c) Explain different tall column internals.
- (d) Explain types of supports with neat diagram.
- (e) Classification of heat exchangers and evaporators.
- (f) Explain types of losses in storage of volatile liquids.

Q.2 (a) Design a pressure vessel subjected to internal pressure for the following data: **12**

- A) Shell and head data: Design pressure = 0.5 N/mm^2 ,
ID of the shell = 1000 mm
Permissible stress for shell material = 140 N/mm^2 ,
Corrosion allowance = 2 mm
Weld joint efficiency = 0.85
Crown radius = Shell ID
Knuckle radius = 10 % of shell ID
- B) Flanged joint: Gasket factor = 3.75,
Min gasket seating stress = 52.5 N/mm^2
Flange material same as shell material.
Permissible stress for bolt material = 138 N/mm^2
- C) Nozzle data: Shell side
ID = 150 mm
Nozzle material same as shell material.
Design should include Shell, Nozzle and reinforcement.

Q.2(b) Write the design procedure to calculate the height of the tall column **8**
including the stresses developed in the column.

Q3 (a) Write in detail procedure of Design a U tube heat exchanger. **12**

Q.3 (b) Explain different types jackets with neat diagram. **08**

- Q 4 (a)** Design Turbine agitator shaft (shaft diameter) for a vessel of 1500 mm diameter with following data: **10**
- Internal pressure in vessel = 0.5 N/mm^2
Diameter of agitator = 500 mm
Speed of agitation = 200 rpm
Specific gravity of liquid in vessel = 1.2
Viscosity of liquid in vessel = 600 cp
Overhang of agitator = 1300 mm
No of blades = 06
Width of blade = 75 mm
Thickness of blade = 8 mm
No of baffles = 04
Shear stress in shaft = 55 N/mm^2
Elastic limit in tension = 246 N/mm^2
Modulus of elasticity = $1.95 \times 10^5 \text{ N/mm}^2$
Power no = 4.5
Density of shaft material = 7580 kg/m^3
Consider Gland loss = 5%, power transmission loss = 5%
- Q 4(b)** Write the design procedure for a Standard Vertical Short Tube Evaporator for the following data- **10**
- Design should include-
- (a) Diameter of tube sheet,
 - (b) Calandria sheet thickness,
 - (c) Tube sheet thickness,
 - (d) Evaporator drum thickness and diameter,
- Q 5(a)** Explain with neat diagram different types of agitators and their applications. **10**
- Q 5(b)** A cylinder has an ID of 100 mm and an internal pressure of 50MPa. Find the needed wall thickness if the factor of safety is 2.0 and the yield stress is 250 MPa. Use the maximum shear stress theory. **10**
- Q.6 (a)** List out types of NDT method. Explain any one detail with neat diagram. **10**
- Q 6 (b)** Explain different types of roofs in storage tank. **10**