

Duration:[03 Hours]**[Total Marks: 80]****N. B :** (1) Question no.1 is **Compulsory**.(2) Solve any **THREE** from question no.2 to 6.

(3) Use illustrative diagrams wherever possible.

(4) Assume suitable data if necessary and mention it clearly.

Q.1 Solve **Any Four** questions :

- a) Name the various modes of heat transfer and also explain its governing laws. **5**
- b) What do you understand by 'Fin' ? Enlist the various types of fin? Also draw sketches for any three types of fins. **5**
- c) State and Explain the following radiation laws- **5**
- i) Planck's law
- ii) Kirchoff's law
- d) Differentiate between Four stroke cycle and Two stroke cycle engines. **5**
- e) State the modes of Mass Transfer. State & explain the Fick's law of diffusion. **5**

- Q.2** a) The wall of a cold storage consists of three layers-an outer layer of ordinary bricks, 0.25m thick, a middle layer of cork, 0.1m thick and an inner layer of cement, 0.06m thick. The thermal conductivities of the materials are 0.7W/m.K, 0.043W/m.K and 0.72W/m.K, respectively. The temperature of the outer surface of the wall is 30°C and that of inner is -15°C. Calculate: **10**
- i) Steady state rate of heat gain per unit area
- ii) Temperature at the interfaces of composite wall
- iii) The percentage of total heat resistance offered by individual layers
- b) Derive an expression for log mean temperature difference (LMTD) in a parallel flow heat exchanger. State your assumptions. **10**

- Q.3** a) Water at the rate of 0.8 kg/s at 90°C flows through a steel pipe having 25mm ID and 30mm OD passing through the room. The outside surface temperature of the pipe is 84°C and temperature of the surrounding air is 20°C. The room pressure is 1 atm and the pipe is 15m long. How much heat is lost by free convection in the room.? **12**

You may use correlation

$$Nu = 0.53 (Gr.Pr)^{0.25} \text{ for } 10^4 < Gr.Pr < 10^9$$

$$= 0.10 (Gr.Pr)^{1/3} \text{ for } 10^9 < Gr.Pr < 10^{12}$$

Take the properties of air as

$$\mu = 1.9606 \times 10^{-5} \text{ kg/ms, } k = 13.02 \text{ W/m}^{\circ}\text{C, } \rho = 1.0877 \text{ kg/m}^3, C_p = 1007.3$$

J/kg.K

$$k = 0.02813 \text{ W/m.K,}$$

- b) One end of the copper rod 15 cm long and 0.6 cm in diameter is connected to a wall maintained at 300°C and the other end protrudes into a room whose air temperature is 20°C. If the tip of the rod is insulated, Estimate -i) Heat loss by the rod. ii) The heat transfer efficiency of copper rod. Take $h = 28 \text{ W/m}^2\text{K}$, $k = 370 \text{ W/mK}$. **08**

- Q.4 a)** In an open heart surgery, under hypothermic conditions, the patient blood is cooled before the surgery and rewarmed afterwards. It is proposed that a concentric tube, counter flow heat exchanger of length 0.5 m be used for this purpose with the thin walled inner tube having a diameter of 55mm. If the water at 60°C and 0.10 kg/s is used to heat the blood entering the heat exchanger at 18°C and 0.05kg/s, what is the temperature of blood leaving the heat exchanger? The overall heat transfer coefficient is 500W/m².K and specific heat of the blood is 3500J/kg.K, Specific heat of water is 4200 J/kg.K **10**
- b)** Explain the stages of combustion in SI engines with the help of pressure - crank angle diagram. **10**
- Q.5 a)** In a test of single cylinder four stroke oil engine with Bore 300mm and Stroke 450 mm , the following observations were made: **12**
- | | |
|--|----------------|
| Duration of Test | = 60 min |
| Engine speed | = 200 RPM |
| Fuel consumption | =7 kg |
| Calorific value of fuel | = 45000 kJ/kg |
| Average speed | =200 rpm |
| Indicated mean effective pressure | =5.867 bar |
| Net Brake load | =130 kg |
| Brake drum diameter | =1650 mm |
| Total weight of jacketed of cooling water | = 500 kg |
| Temperature rise of jacketed cooling water | =40°C |
| Temperature of exhaust gases | =300°C |
| Air consumption | =300kg |
| Specific heat of exhaust gases | =1.004kJ/kg.K, |
| Specific heat of water | = 4.19 kJ/kg.K |
| Room temperature | =25°C |
- Determine: i) Mechanical Efficiency ii) Brake thermal efficiency iii) Draw up heat balance sheet on minute and percentage basis
- b)** What do you understand by the hydrodynamic and thermal boundary layer? Illustrate with reference to flow over a flat heated plate. **08**
- Q.6 (a)** A solid copper sphere of 10 cm diameter ($\rho = 8954 \text{ kg/m}^3$, $C_p=383 \text{ J/kg.K}$, $k= 386 \text{ W/mk}$) ,initially at a uniform temperature $t_i=250^\circ\text{C}$, is suddenly immersed in a well stirred fluid which is maintained at a uniform temperature $t_a=50^\circ\text{C}$.The heat transfer coefficient between the sphere and the fluid is $h= 200 \text{ W/m}^2\text{K}$.Determine the temperature of the copper sphere at $\tau =5 \text{ min}$ after the immersion. **08**
- b)** With a neat sketch explain the construction and working of Simple Carburetter. **06**
- c)** Enumerate various methods to control engine emission. Explain any one method in brief with neat sketch. **06**
