## Paper / Subject Code: 42571 / Power Electronics

| Durat      | tion: 3hrs [Max Marks: 80]  | ,            |
|------------|---|--------------|
| N.B.:      | <ol> <li>Question No 1 is Compulsory.</li> <li>Attempt any three questions out of the remaining five.</li> <li>All questions carry equal marks.</li> <li>Assume suitable data, if required and state it clearly.</li> </ol> |              |
| 1          | Attempt any FOUR  | [20]         |
| a          | Draw the characteristics of TRIAC and what are the applications of TRIAC?   | d <b>5</b> ] |
| b          | Compare Forced commutation and Natural commutation of SCR.  | [5]          |
| c          | Explain the significance of freewheeling diode in controlled rectifiers.  | [5]          |
| d          | What are the different triggering methods? Describe any one method.   | [5]          |
| e          | Explain the block diagram of SMPS.  | [5]          |
| 2 a        | Explain latch-up phenomenon in IGBT. How it can be overcome?  | [10]         |
| b          | Explain synchronized UJT relaxation oscillator circuit to trigger SCR.  | [10]         |
| 3 a        | Explain Half Wave Controlled Rectifier for inductive load   | [10]         |
| b          | Draw VI characteristics of SCR and explain in brief all conducting states.  | [10]         |
| <b>4</b> a | List the advantages and disadvantages of the Buck and Boost converter.  | [10]         |
| <b>b</b>   | Explain in detail the multiple pulse waves modulating (PWM) technique for single-phase inverters.   | [10]         |
| 5 a        | Explain continuous mode fly-back converter with appropriate waveform.   | [10]         |
| b          | Draw and explain boost converter feeding an inductive load (R-L) with neat diagram and waveforms. Derive the expression for output voltage.   | [10]         |
| 6 a        | Explain the working of single phase cycloconverter with circuit diagram and waveforms.  | [10]         |
| b          | Discuss the significance of, various performance parameters for DC-AC converters. Derive the formula for Harmonic Factor, THD and Displacement Factor.  | [10]         |

\*\*\*\*\*\*

55306